

Basler

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Basler Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Basler Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Decs-250n Cn1sn1n	Negative Forcing Digital Excitation Control System, 120 Vac/125 Vdc, Low (50/60 Hz), 100Base-T (ModbusTCP)
ICRM-15	Inrush Current Reduction Module
DECS-250	24/48VDC, Internal Autotracking Only, Compression Type Terminals, 100Base-T (Modbus™ TCP), PROFIBUS
DECS-250 CN1SN1N	Digital Excitation Control System, 125 Vac/Vdc, Internal Autotracking Only, Spring Type Terminals, 100Base-T (Modbus™ TCP)
DECS-100 B05	VAR/PF Controller, V, 5 Amp CT secondary
acA1300-75gc	
acA3088	+ 3Meter USB Cable
	Digital Excitation Control System, 24/48 Vdc, Internal/External

DECS-250 LN2CN1P	Autotracking, Compression Type Terminals, 100Base-T (Modbus™ TCP), PROFIBUS
DECS-250 LN1CN1P	DECS-250 24/48VDC, Internal Autotracking Only, Compression Type Terminals, 100Base-T (Modbus™ TCP), PROFIBUS
ES-27/59 3AB1N0N0	Under/Overvoltage Relay, Three-Phase, Three Wire, 120 Vac Nominal Input , Adjustable, 0 to 20 seconds, 50/60Hz
ICRM-1S	Inrush Current Reduction Module
DECS-100 B11	
DECS-100 B15	
DECS-250N LN1SN1N	
ES-74S 7NB0G4N0	
ICRM-7	
TBC	
DECS 250CN1SN1N	VOLTAGE REGULATOR DECS250
ICRM 15	ICRM15 MODULE DECS250 ACCESSORIES
DECS-250 LN2SN1N	AVR DIGITAL EXCITATION CONTROL SYSTEM DECS250
DECS150	Plate+AVR
2000036233	USB 3.0 Interface Card PCIe, Fresco FL1100, 4HC, x4, 4 Ports 92395.2170.GP2,L,V,G, XX.\..172230-101..T.PLM: DWG-00175775
ES-59 3SB1N0N100	ES-59 OVERVOLTAGE RELAY, THRE PHASE, 3 WIRE, SPECIAL VOLTAGE, ADJUSTABLE 0-20 SECONDS, 50/60HZ
E02246209	
color 1/2.3" USB3.0	107821 a2A1920-160ucBAS 1920 x 1200, 160 fps,
2200000568	Lens Basler C23-0824-5M 2/3", 8 mm, F2.4, 5 Mpix
2000033241	Cable USB 3.0, Micro B screw lock/A, 5 m
SN: 22245088	
DECS-250 LN1SN1N	Digital Excitation Control System, 24/48 Vdc, Internal Autotracking Only, Spring Type Terminals, 100Base-T (Modbus™ TCP)
ES-25 1EA1N1N0	Sync-Check Relay, Single phase, 415 Vac Nominal Input, Timing instantaneous, 50/60 Hz, Close on Dead Bus
AVC125-10 A1	VOLTAGE REGULATOR Sensing Voltage 100/120 Vac, Sensing Frequency 50/60Hz
BAS-ACC-CBL-2000031224	Basel accessory cable Power I/O Cable M5 4p/open, 10 m for

cameras: ace CI	
DECS-200 DIGITAL EXCITATION CONTROL	
BEI-64F GROUND FAULT RELAY	
DECS-250 CN2SN1N	Digital Excitation Control System, Power Supply: 125 Vac/Vdc, PSS: None, Autotracking: Internal/External Autotracking, Terminals: Spring Type Terminals, Synchronizer: None, Ethernet Communications: 100Base-T (Modbus TCP), Additional Communication Protocol: None
DECS-250 CN1CN1N	Digital Excitation Control System, 125 Vac/Vdc, Internal Autotracking Only, Compression Type Terminals, 100Base-T (Modbus™ TCP)
DECS-200, DIGITAL EXCITATION CONTROL SYS	
DECS200	
DECS-150 1NS1V1B1S	Digital Excitation Control System, 125 Vac/Vdc, Internal Autotracking Only, Compression Type Terminals, 100Base-T (Modbus™ TCP)
acA1920-50gm	ID:107759-06 S/N:24262293
DECS-250 LN1SN1N	Digital Excitation Control System, 24/48 Vdc, Internal Autotracking Only, Spring Type Terminals, 100Base-T (Modbus™ TCP)
Decs250	
Avc63-12-A1 (Ex. K63-12b)	
L301kc	
Decs-100	
Cbs 212a	
Aca1300-30gm	
Be3-59t-V	
747-Lm28lf	
Mco2107	
Avc125-10-B1	
Icrm-15	
Avc125-10a1	
Decs-400	
Decs-250 Ln1sn1n	Digital Excitation Control System, 24/48 Vdc, Internal Autotracking Only, Spring Type Terminals, 100Base-T (Modbus™ TCP)

Be1-11g	G6D3M0J2P0E000 Generator Protection System, Dual 5 Amp Nominal, Dual Ground - 5 Amp Nominal, 24 Vdc, Modbus, Vertical (S1 sized) Case, Standard I/O, Normally-Closed Alarm, Current Differential, Copper Ethernet
9116300109(Ex9057900100)	
Decs-250n	
Decs125-15	
Decs-15	
Ral6144-16gm	
A-Ace-1300-60gc	
Be1-25, M1e-A7p-N5u6f	
Es-27/59 3sb1n0n100	Under/Overvoltage Relay Sensing Input Type: Three-Phase, Three Wire Input: Special Voltage 100V Timing: Adjustable, 0 to 20 seconds Frequency:50/60 Hz
Idp-801	
Avc125-10 A1	VOLTAGE REGULATOR Sensing Voltage 100/120 Vac, Sensing Frequency 50/60Hz
Decs-200n	
Be1-25a, A2-F5-V3-D0	
Be1-25-M1e-A7p-N5u6f	