

Re S.P.A.

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Re S.P.A. Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Re S.P.A. Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
01A02008	Brake pad for Combiflex brake Type CX.01A67016-R15.AR3 with patented noise filter Coefficient of friction : 0.35 (standard)
CF.085.0100.40.2RS mA EVO	07.06A08011.00 Load cell as flange version Output : 4-20mV Control range : 0 - 100 kg Protection class: IP 53 !!!!! WITHOUT plug !!!! CODE: 6A08036
07.04B03009.00	Web edge control with ultrasonic sensor Type WG.0255.0160.0200.050.W-LIGO microprocessor controlled Complete with 1* Control Rack 2* pulleys 1* control unit type W-LIGO 1* ultrasonic sensor type SU.m-25 V2 1* sensor holder 1* cable set Technical specifications : Temperature : 0 - 50.00 °C Voltage : 24 Vdc Web tension max. : 150.00 N Adjustment range : +/- 10.0 mm Accuracy : +/- 0.10mm Roller length : 160 mm Working width max. : 100 mm Roller distance : 200 mm Roller diameter : ø50 mm Control roller: aluminum (optionally available with cork or rubber coating)
	Web edge control with ultrasonic sensor Type WG.0255.0200.0200.050.W-LIGO microprocessor controlled Complete with 1* Control Rack 2* pulleys 1* control unit

07.04B03009.00	type W-LIGO 1* ultrasonic sensor type SU.m-25 V2 1* sensor holder 1* cable set Technical specifications : Temperature : 0 - 50.00 °C Voltage : 24 Vdc Web tension max. : 150.00 N Adjustment range : +/- 10.0 mm Accuracy : +/- 0.10mm Roller length : 200 mm Working width max. : 140 mm Roller distance : 200 mm Roller diameter : ø50 mm Control roller: aluminum (optionally available with cork or rubber coating)
07.04B03009.00	Web edge control with ultrasonic sensor Type WG.0255.0400.0300.050.W-LIGO microprocessor controlled Complete with 1* Control Rack 2* pulleys 1* control unit type W-LIGO 1* ultrasonic sensor type SU.m-25 V2 1* sensor holder 1* cable set Technical specifications : Temperature : 0 - 50.00 °C Voltage : 24 Vdc Web tension max. : 150.00 N Adjustment range : +/- 10.0 mm Accuracy : +/- 0.10mm Roller length : 400 mm Working width max. : 340 mm Roller distance : 300 mm Roller diameter : ø50 mm Control roller: aluminum (optionally available with cork or rubber coating)
06.04253004.00	Brake caliper with brake pads Type CX.4253004 without flow brake valve and compressed air distributor Braking power: 100% Identification color: black
01D38011	
06.01A14023.00	Fan housing HP3 with fan for CX.250 Type RE.CX.01A14077-HP3 (V2) Voltage: 24 VDC Power: 50W Current consumption: 2.5 A Complete with fan housing HP3
Cx 250	
Ck.125.150.25 Acc	
11456. 1209 999-802-0206	
R15 999-800-0322	
Re Druckmessdose Cf.85.200.40.2rs	
Mega N090.01a	
Cf.85.15.40.2rs Ma Evo	
999-801-5105	
999-802-0208	
TI.01/SI.3	
B.651	
Cf.120.25.52.2rs	
999-800-0136	
999-802-0031	
SI3-Replaced By TI.01	
999-800-0134	

Mod. T-One Sn 00166.0906
999-802-1204
999-800-0106
Re Druckmessdose Ck.175.300.35
999-802-0212
999-802-0226
Re Druckmessdose Ck.175.300.35 All
Re-S-P-A-C650ralte-Ausf3;Hrungneue-Ausf3;Hrung-C651r-Istanbul-Turkiye
999-800-0113
10073065
999-802-0056
999-800-0307
TI.01
C.651.R
Cf.85.100.40.2rs
999-800-0135
999-802-1005
Cf.85.50.40.2rs
999-802-0247
999-800-0114
999-802-1021