

Roemheld

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Roemheld Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Roemheld Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Artikel-Nr. 2954410	Sequence valve NW 4 - G1 / 4 with check valve Setting range: 10 to 75 bar Max. 500 bar, as per data sheet C2.954 Net single weight: 0.48kg
Artikel-Nr. 8601211	Air hydraulic tensioning pump for single-acting cylinders max.flow rate 0.85 l / min The air hydraulic clamping pump is Delivered ready for connection with oil filling. max. 500 bar, as per data sheet D8.602 Net single weight: 7.5kg
Artikel-Nr. 2953111	Pressure control valve Seat valve without overpressure function Pipe connection Setting range: 10/30 to 380 bar max. 500 bar, as per data sheet C2.9533 Net single weight: 1.15kg
1545265	Block cylinder, double acting Piston rod with external thread Piston Ø 40 mm, stroke 50 mm Connection pipe thread G1 / 4, seals NBR 2 transverse and 4 longitudinal holes max. 500 bar, as per data sheet B1.542 Net single weight: 3.65kg
1846A090R36M	Swing clamp with robust swing mechanism, double acting, flange above, without query, max.tension force 27.5 kN, Ø 45/32 mm, Clamping stroke 15 mm, swing stroke 21 mm,

	Swivel angle 90 ° right, with metal wiper, max. 350 bar, as per data sheet B1.853. Net single weight: 6.05kg
1846A090L36M	Swing clamp with robust swing mechanism, 90 °, counterclockwise, double acting, flange on top, without query, max.tractive force 27.5 kN, Ø 45/32 mm, clamping stroke 15 mm, Swing stroke 21 mm, with metal wiper, max. 350 bar, according to data sheet B1.853. Net single weight: 6.05kg
2951416	Check valve, releasable, flange design, without pre-relief, max. 20 l / min, max. 500 bar, according to data sheet C2.9512. Net single weight: 0.233kg
2953110	Pressure control valve Seat valve without overpressure function Flange or pipe connection Setting range: 10/30 to 380 bar max. 500 bar, as per data sheet C2.9533
9606102	Hydraulic accumulator 13 ccm Gas preload pressure: 100 bar Connection: G1 / 4 male thread max. 400/300 bar, as per data sheet F9.601
1545265	Block cylinder, double acting Piston rod with external thread Piston Ø 40 mm, stroke 50 mm Connection pipe thread G1 / 4, seals NBR 2 transverse and 4 longitudinal holes max. 500 bar, as per data sheet B1.542 Net single weight: 3.65kg
0131213	Sealing set NBR for for 1545-265 according to data sheet S0.001
Artikel-Nr. 1891101	Swing clamp with overload protection Screw-in version, double acting Rod Ø 20 mm, swivel angle 90 ° to the right Clamping stroke 7 mm, swing stroke 7 mm max. 500 bar, according to data sheet B1.891 Net single weight: 0.461kg
2954410	Connection valve NW 4 - G1 / 4 with check valve Setting range: 10 to 75 bar max. 500 bar, as per data sheet C2.954
BCC1080H036SZ	Bore clamp Ø 8 mm Clamping range Ø 7.8 - 8.8 mm Support height H: 36 mm max.clamping force approx .: 3.3 kN max.radial expansion force approx .: 9 kN pneumatic support and clamping control double acting, sealing air connection max. 80 bar, as per data sheet B1.487
BCE1080H085SZ	Bore clamp, eccentric Ø 8 mm Clamping range Ø 7.7 - 8.7 mm Support height 85 mm max.clamping force: 3.3 kN pneumatic support and clamping control double acting, sealing air connection max. 80 bar, according to data sheet B1.486
1942900	Screw-in work support M26 x 1.5 mm, single acting, Metal wiper edge, pin Ø 16 mm, pin stroke 6.5 mm, max.load force 4 kN, function type: oil pressure with spring force, max. 350 bar, as per data sheet B1.9405.
1947200	Screw-in work support M30 x 1.5 mm single-acting, metal wiper edge Bolt Ø 12 mm, bolt stroke 8 mm max.load force 4.0 kN Function type: oil pressure with spring force max. 70 bar, according to data sheet B1.9470

1826G7131	Lever clamp 70 bar, double-acting Size 1, clamping direction G with throttle valve without shift rod with clamping lever with pressure screw max. 70 bar, as per data sheet B1.8268
1458001	Screw-in cylinder, single acting, Ø 8mm, stroke 5 mm, max. 500 bar, according to sheet B1.458. Net single weight: 0.02kg
HYDROFIX HAWE BATTERY BLOCK ASSY	
15431037	Block cylinder, similar to 1543-195, according to data sheet B1.5094, however housing dimensions 39 x 65 mm, Piston Ø 25/16 mm, stroke 100 mm, Total length 151 mm, max. operating pressure 400 bar
RO.1462-610	
1543105B	Block cylinder, double-acting Piston Ø 25 mm, stroke 20 mm Flange connection B, seals NBR 4 longitudinal bores max. 500 bar, according to data sheet B1.5094 Net single weight: 1.25kg
15431003	block cylinder double acting Piston Ø 25/16 x 50 mm stroke with special housing maximum operating pressure 400 bar according to E-15431003 according to data sheet B1.5094
1846L090R36	Swing clamps with robust swing mechanism double-acting, bottom flange, without query max. pulling force 27.5 kN, Ø 45/32 mm Clamping stroke 15 mm, swing stroke 21 mm Swivel angle 90° right, without metal wiper max. 350 bar, according to data sheet B1.854
1545165	Block cylinder, double-acting, piston Ø 40 mm, stroke 50 mm, Connection pipe thread G1/4, seals NBR, 2 transverse and 4 longitudinal bores, max. 500 bar, according to data sheet B1.5094
1543105	block cylinder double-acting, piston Ø 25 mm, stroke 20 mm, Connection pipe thread G1/4, seals NBR, 2 transverse and 4 longitudinal bores, max. 500 bar, according to data sheet B1.5094.
1536136	Block cylinder, double-acting for end position control Piston Ø 50 mm, stroke 25 mm Connection pipe thread G1/4, seals FKM 2 transverse and 4 longitudinal bores max. 500 bar, according to data sheet B1.520 Net single weight: 4.921kg RGR R
1955022	Screw-in support element M60 x 1.5 mm single-acting, metal wiper edge Bolt Ø 32 mm, bolt stroke 16 mm maximum load 42 kN Type of function: oil pressure with spring force max. 500 bar, according to data sheet B1.9501 RGR R
Retractable nipple - 7000 100	
Retractable nipple - 7000 1001	
Retractable nipple - 7000 102	
Block cylinder, double-acting, piston Ø 40 mm, stroke 50 mm,	

1545165	Connection pipe thread G1/4, seals NBR, 2 transverse and 4 longitudinal bores, max. 500 bar, according to data sheet B1.5094.
1756004	hollow piston cylinder single-acting with spring return Piston Ø 50 mm, stroke 12 mm max. 500 bar, according to data sheet B1.7441
4312202	2-point centering and clamping element double acting max. clamping force 17 kN Clamping Ø 90-98 mm max. 250 bar, according to data sheet H4.305
1953322	Work support, flange design at top single-acting, metal wiper edge Bolt Ø 20 mm, bolt stroke 12 mm maximum load 16.8 kN Type of function: oil pressure with spring force max. 500 bar, according to data sheet B1.9503
9425021	Clutch unit, complete for double-acting cylinders Nominal volume 75 cm ³ Gas preload pressure 100 bar Operating pressure range 110 - 500 bar according to data sheet F9.425
2365001	Directional valve combinations NW 4 manually operated, double-acting for 1 clamping circuit max. 500 bar, according to data sheet C2.345
9208181	throttle banjo fitting, Version A: tube Ø 8 mm - G1/4, max. 500 bar, according to data sheet C2.9501, replaces 9208-129.
1826G7432	Lever clamp 70 bar, double-acting Size 4, clamping direction G with throttle valve without shift rod with a long clamping lever max. 70 bar, according to data sheet B1.8268
3456042	Mounting flange G1/4 for 4312-0XX/-1XX max. 250 bar, according to data sheet H4.305
4312025	3-point centering and clamping element double acting max. clamping force 10 kN Clamping Ø 25-29 mm max. 250 bar, according to data sheet H4.305
4312000	2-point centering and clamping element double acting max. clamping force 10 kN Clamping Ø 25-29 mm max. 250 bar, according to data sheet H4.305
1942501	Screw-in support element M48 x 1.5 mm single-acting, metal wiper edge with spring chamber ventilation Bolt Ø 28 mm, bolt stroke 10 mm maximum load 23.5 kN Type of function: oil pressure with spring force max. 500 bar, according to data sheet B1.943
2954410	Sequence valve NW 4 - G1/4 with check valve Setting range: 10 to 75 bar max. 500 bar, according to data sheet C2.954
1942-501	Ø28 M48X1,5 500 BAR
2954-410	
2954429	Sequence valve NW 4, can be flanged on with check valve Setting range: 10 to 150 bar max. 500 bar, according to data sheet C2.954

2954420	Sequence valve NW 4 - G1/4 with check valve Setting range: 10 to 150 bar max. 500 bar, according to data sheet C2.954 Net single weight: 0.48kg
1947200	Screw-in support element M30 x 1.5 mm single-acting, metal wiper edge Bolt Ø 12 mm, bolt stroke 8 mm max. load force 4.0 kN Type of function: oil pressure with spring force max. 70 bar, according to data sheet B1.9470 Net single weight: 0.25kg
1545195	Block cylinder, double-acting Piston Ø 40 mm, stroke 100 mm Connection pipe thread G1/4, seals NBR 2 transverse and 4 longitudinal bores max. 500 bar, according to data sheet B1.5094
9425021	Clutch unit, complete for double-acting cylinders Nominal volume 75 cm3 Gas preload pressure 100 bar Operating pressure range 110 - 500 bar according to data sheet F9.425
1857T090L29	Swing clamps with robust swing mechanism double-acting, top flange, without query max. pulling force 16.1 kN, Ø 65/36 mm Clamping stroke 10 mm, swing stroke 19 mm Swivel angle 90° left, without metal wiper max. 70 bar, according to data sheet B1.8500 Net single weight: 6.9kg
1544-265	Block cylinder, double-acting Piston rod with external thread PistonØ 32mm, stroke 50mm Connection pipe thread G1/4, seals NBR 2 traverse 4 longitudinal bores max. 500 bar, according to data sheet B1.542
0155-400	Bearing block for 154426X BearingØ 20 H7mm according to data sheet G3.810
3890-017	Rod end M16 x 1.5mm BearingØ 20 H7mm according to data sheet G3.810
Cylinder	VOLLSPANNZYLINFER CylinderOVS 130 443194 KOLBENDURCHGANG 18MM/HUBKONTROLLE F90
6851201	Directional valve combinations NW 4 manually operated, single-acting for 1 clamping circuit max. 500 bar, according to data sheet C2.345
0354982 SEAL SET POSITION CONTROL	1829 7X3 DXX
2953112	pressure control valve Poppet valve without overpressure function pipe connection Setting range: 8 to 130 bar max. 500 bar, according to data sheet C2.9533
1460101	Screw-in cylinder, single-acting Ø 12 x 10 mm stroke, with piston thread max. 500 bar, according to Sheet B1.461
1460101	Screw-in cylinder, single-acting Ø 12 x 10 mm stroke, with piston thread max. 500 bar, according to Sheet B1.461 Net single weight: 0.089kg/piece
1544165	Block cylinder, double-acting PistonØ 32mm, stroke 50mm Connection pipe thread G1/4, seals NBR 2 traverse 4 longitudinal bores max. 500 bar, according to data sheet B1.5094

6851201	Directional valve combinations NW 4 manually operated, single-acting for 1 clamping circuit max. 500 bar, according to data sheet C2.345
7000 100 SPIGOT	
7000 101 SPIGOT	
7000 102 SPIGOT	
1547105	Block cylinder, double acting, piston Ø 63 mm, Stroke 30 mm, connection pipe thread G1/2, seals NBR, 2 transverse and 4 longitudinal holes, max. 500 bars, according to catalog sheet B1.5094.
0131166	Sealing set NBR for 13471X5, 15471X0, 15471X5, 154741X, 154745X, 154751X, 154755X and 1577105 according to catalog sheet S0.001 A return of delivered seals is possible due to our internal Unfortunately, quality criteria are not possible
9384765	Quick release coupling, complete coded blue NW 5, connection thread G1/4 PushPull, seals FKM max. 500 bar, according to catalog sheet F9.381
2953-111	Pressure control valve Seat valve without overpressure function Pipe connection Setting range: 10/30 to 380 bar max. 500 bar, according to catalog sheet C2.9533
1461100	Screw-in cylinder, single-acting Ø 16 x 12 mm stroke max. 500 bar, according to sheet B1.461
Hc2-2.8-B-1	
1845A090R30D	Swing clamp with robust swing mechanism double acting, flange at top, without query max. tensile force 18.4 kN, Ø 36/25 mm Clamping stroke 15 mm, swivel stroke 15 mm Swivel angle 90° right, without metal scraper max. 350 bar, according to catalog sheet B1.853
1845L090L30	Swing clamp with robust swing mechanism double acting, bottom flange, without query max. tensile force 18.4 kN, Ø 36/25 mm Clamping stroke 15 mm, swivel stroke 15 mm Swivel angle 90° left, without metal scraper max. 350 bar, according to catalog sheet B1.854
9384755	Quick release coupling, complete coded green NW 5, connection thread G1/4 PushPull, seals FKM max. 500 bar, according to catalog sheet F9.381
1461100	Screw-in cylinder, single-acting Ø 16 x 12 mm stroke max. 500 bar, according to sheet B1.461
9384745	Quick release coupling, complete coded yellow NW 5, connection thread G1/4 PushPull, seals FKM max. 500 bar, according to catalog sheet F9.381
	Quick release coupling, complete black coded NW 5,

9384715	connection thread G1/4 PushPull, seals FKM max. 500 bar, according to catalog sheet F9.381
9384735	Quick release coupling, complete coded red NW 5, connection thread G1/4 PushPull, seals FKM max. 500 bar, according to catalog sheet F9.381
9384765	Quick release coupling, complete coded blue NW 5, connection thread G1/4 PushPull, seals FKM max. 500 bar, according to catalog sheet F9.381
9384755	Quick release coupling, complete coded green NW 5, connection thread G1/4 PushPull, seals FKM max. 500 bar, according to catalog sheet F9.381
1896203	Swing clamp with overload protection Top flange, double acting Swivel angle 90° left Piston Ø 50 mm, rod Ø 40 mm Clamping stroke 15 mm, swivel stroke 11 mm max. 500 bar, according to catalog sheet B1.880
1544165	Block cylinder, double acting Piston Ø 32 mm, stroke 50 mm Connection pipe thread G1/4, seals NBR 2 transverse and 4 longitudinal holes max. 500 bar, according to catalog sheet B1.5094
1541165	Block cylinder, double acting Piston Ø 16 mm, stroke 50 mm Connection pipe thread G1/4, seals NBR 2 transverse and 4 longitudinal holes max. 500 bar, according to catalog sheet B1.5094
1461001	Screw-in cylinder, single-acting Ø 16 x 12 mm stroke with piston thread max. 500 bar, according to sheet B1.460
1947200	Screw-in support element M30 x 1.5 mm simple acting, metal scraper edge Bolt Ø 12 mm, bolt stroke 8 mm max. load force 4.0 kN Function type: oil pressure with spring force max. 70 bar, according to catalog sheet B1.9470
9284036	Rotary union NW 5, 4-wire max. 500 bar, according to catalog sheet F9.280
HD.01184 2 DOUBLE ETK 3 CON EL SAND HYDR ÜN	
RO.9284-036 HYDRAULIC ROTARY DISTRIBUTOR	
RO.2954-420 HYDRAULIC SEQUENCE VALVE	
RO.2953-111 PRESSURE VALVE	
2954420	Switching valve NW 4 G1/4 with check valve Setting range: 10 to 150 bar max. 500 bar, according to catalog sheet C2.954
2953111	Pressure control valve Seat valve without overpressure function Pipe connection Setting range: 10/30 to 380 bar max. 500 bar, according to catalog sheet C2.9533

Z804209	
Z804230	
Z804238	
1345195	Universal cylinder, double acting Ø 40 x 100 mm stroke External thread M 65 x 1.5 max. 500 bar, according to sheet B1.309
9846000	Pressure gauge 0 – 600 bar with glycerin filling with locking screw SW 9 Connection G1/4 according to catalog sheet F9.300 Net – individual weight: 0.302kg/piece
0354975	Clamping lever, length L=24 mm for flat lever clamp size 2 Net – individual weight: 0.0953kg/piece
1829620E00	Flat lever clamp Size 2, single acting max. clamping force: approx. 3.5 kN without position control without tension lever max. 250 bar Net – individual weight: 0.573kg/piece
1940900	Screw-in support element, M26 x 1.5 mm, single acting, metal scraper edge, bolt Ø 16 mm, Bolt stroke 6.5 mm, max. load force 4 kN, Function type: spring force, max. 350 bar, according to catalog sheet B1.9405. Net – individual weight: 0.153kg/piece
8819001	Screw pump block design, displacement 21 cm³, Stroke volume/revolution 0.98 cm³, stroke 43 mm, Installation position horizontal, max. 500 bar, according to catalog sheet D8.819. Net – single weight: 2.14kg/piece
1844A090R24D	Swing clamp with robust swing mechanism double acting, flange at top, without query max. tensile force 10.5 kN, Ø 28/20 mm Clamping stroke 12 mm, swivel stroke 12 mm, Swivel angle 90° right, without metal scraper max. 350 bar, according to catalog sheet B1.853 1844A090R24 has been replaced by 1844A090R24D
3527014	Nut, M18 x 1.5 mm, according to catalog sheet B1.880
1545870	Block cylinder, double acting, Piston Ø 40/25 mm, stroke 25 mm, Connection pipe thread G1/4, seals FKM, Version according to catalog sheet B1.5094, similar to 1545106, however 4 longitudinal holes with bottom side screw head countersinks, with coupling pin 3614236, max. operating pressure 350 bar.
1541-166-501f	
84662020	
Ro 1845 A090r30	
1345195	
1315-026	
1846I090I36 Schwenkspanner Mit Robuster Schwenkmechanik	

1551-005	
576g-811m14-943fg	
0460729	
577g-1193m14-944g	
Asm02001	
1463-610	
2953-111	
1475-11	
0353-808	
1544-105	
0131264	
Fcu1000	
1541-100-101f	
1942-501	
0131xxx	
1545513 Blockzylinder, Doppelt Wirkend Mit Aluminiumgehäus	
3614075	
0354003	
1955-000	
Ro 2953 112	
1474-001	
1845I090r30 Schwenkspanner Mit Robuster Schwenkmechanik	
1545-090 Blockzylinder Dw	
S724-02342	
9284036	Rotary union NW 5, 4-wire max. 500 bar, according to data sheet F9.280 Netto – Einzelgewicht: 4,6kg
1475011	
1955322	
3829-099	
1431-001	

1461-101
1541-105
Ro 1461 101
4316160
1845a090r30 Schwenkspanner Mit Robuster Schwenkmechanik
8755028
Stc0605-Bt30
1451000
Ro 1845 L090l30
9284-036
1462-101 Threaded Body Cylinder
1846-D090-R36m
3829-234
1541-161-508f
1846d090r36m
0460836
Hc2-2.8-B-1
1857a090r29m
Ro 1845 L090r30
1543105s
1541-908-206r
1461101 Einschraubzylinder
Ro 1846 L090l36
377ag-811m14-427eg
Ro.1845-A090r30 Swing Clamp 90°
1883103
2953111
0460831
Ro.1846-L090l36 Swing Clamp 90°
1857a090l29m

[1845I090I30 Schwenkspanner Mit
Robuster Schwenkmechanik](#)[Afd1100-2](#)[0131160](#)[1473-001](#)[Ro.1845-L090r30 16](#)[0353814](#)[1546105bcd Blockzylinder](#)[1846d090I36m](#)[0354001](#)[1942501](#)[2951-417](#)[1955-322](#)[2954-440](#)[1883203](#)[1546165 Blockzylinder](#)[Asm01114](#)[1825220p](#)[1345-195](#)[Artikel-Nr. 2174160](#)

Swing clamp double acting with manual override, overload protection and position monitoring Clamping force: 60 kN at 400 bar Swing stroke: 13 mm Clamping and lowering stroke: 5 mm Max. Flow rate: 10 cm³ / s for clamping edge: 18 mm Max. Operating pressure: 400 bar with pipe connection G1 / 4 according to catalog sheet WZ 4.2170

[0131xxx Dichtsatz Für 1545090](#)[Ro.2953-112 Basınc Valfi](#)[2951417](#)[1544513 Blockzylinder, Doppelt Wirkend
Mit Aluminiumgehäus](#)[0460656](#)[1544210c](#)[Par03223](#)[1846-D090-L36m](#)

1825-220p
Ro 1947 400
4316160cs01
1544-210c
1895-203
Ro 2954 410 Hidrolik Valve