

## Sitec-Sieber

Garanti: 12 ay  
 Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.  
**Sitec-Sieber** Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

*Firmamız Sitec-Sieber Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



| rn                           | Aıklama                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">7200211</a>        | Pressure screw 3/8 "and 10 mm HP Vibro according to drawing: 720.0211 Nominal width 1.6, 3 and 5 mm M 20 x 1.5 Width across flats 22 Anti-Vibro                                                                                                                                                                                                                                                                                                                                      |
| <a href="#">7200221</a>        | Pressure ring 3/8 "HP VIBRO according to drawing: 720.0221 Internal thread 3/8 "- 24 UNF LH Anti-Vibro Material: 1.4104 Goods no .: 84818099; Country of origin: CH                                                                                                                                                                                                                                                                                                                  |
| <a href="#">7190116-R-NHEP</a> | Through valve NC, 500 bar, G1 / 4 ", DN = 4 with pneumatic drive Spindle made of 1.4542 with ceramic ball and interchangeable seat for N-heptane commitment O-ring in Viton in contact with the medium Medium temp .: -15 ° C to + 200 ° C with magnet and guide on the cylinder prepared for inductive position indication without reed contact switch                                                                                                                              |
| <a href="#">7190101-LD4R</a>   | Test bench valve NO, 400 bar, DN = 4mm with O-ring connection Spindle made of 1.4542 with ceramic ball and interchangeable seat 17 -4PH Test pressure 450 bar, compressed air requirement: 6 bar Medium: n - Heptane O-rings in the drive in MVQ O-rings in Viton in contact with the medium with magnet and guide on the cylinder prepared for inductive position indication without reed contact switch Item no .: 84814090; Country of origin: CH Replacement for: 719.0101-LD4RK |
| <a href="#">720.0211</a>       | Thrust screw 3/8 "and 10 mm HP Vibro Nominal width 1,6, 3 and 5 mm M 20 x 1.5 Spanner size 22 Anti-Vibro                                                                                                                                                                                                                                                                                                                                                                             |
| <a href="#">771,1001</a>       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

|                            |                                                                                                                                        |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">720.0221</a>   | Thrust ring 3/8 "HP VIBRO 5% / -2.40 according to drawing: 720.0221<br>Internal thread 3/8 "- 24 UNF LH Anti - vibro                   |
| <a href="#">720.0330</a>   | Plug 1/4 "HP Standard + Anti-Vibro                                                                                                     |
| <a href="#">771,1009</a>   |                                                                                                                                        |
| <a href="#">729.5024-2</a> |                                                                                                                                        |
| <a href="#">720.0311</a>   | Thrust screw 1/4 "and 6 mm HP VIBRO according to drawing: 720.0311<br>Nominal width 1.6 and 3 mm M 16 x 1.5 Spanner size 17 Anti-Vibro |
| <a href="#">771,1006</a>   |                                                                                                                                        |
| <a href="#">720.0321</a>   | Thrust ring 1/4 "HP VIBRO according to drawing: 720.0321 Internal<br>thread UNF 1 / 4-28 Anti-Vibro                                    |
| <a href="#">719.0116-K</a> |                                                                                                                                        |
| <a href="#">719.0115-K</a> |                                                                                                                                        |
| <a href="#">771,1002</a>   |                                                                                                                                        |
| <a href="#">7280300-10</a> |                                                                                                                                        |
| <a href="#">7280722</a>    |                                                                                                                                        |
| <a href="#">770,2100</a>   |                                                                                                                                        |
| <a href="#">771,1017</a>   |                                                                                                                                        |
| <a href="#">7700,1100</a>  |                                                                                                                                        |