



Yamatake

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin

info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaőabilirsiniz. **Yamatake** Markası, tedarik sresi iin ltfen bizimle iletiőime geiniz.

Firmamız Yamatake Trkiye Distribtr veya temsilcisi deėildir. Firmamız sipariő durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Avp302-Lsd2d-Xxxxx	Smart Valve Positioner 300 Series Analog Signal(4 to 20mA.DC.) with HART communication protocol ATEX Intrinsically safe Air piping connection : 1/4 NPT Electrical connection : M20×1.5 Finish : standard (Baked Acrylic) Direct action Supply pressure classification : 150<Ps≤300kPa Scale unit : bar
APM-D3E1	PROXIMITY SENSOR
FL2B-4J6-E	
DIGITAL INDICATING CONTROLLER	CP-UM-1586E SDC31
FL7M-3J6HD-L5	PROXIMITY SENSOR
SL1-E	LIMIT SWITCH
SL1-BK	LIMIT SWITCH
C26TC0UA5200	DIGITAL INDICATING CONTROLLER
83104848-001 + PTM-24F17-01	24V 11MF 50/60 HZ LOT 6A3E 250/300RPM
0548U	
0540U	
1LS10-J	Limit Switch
SL1-P	Mikro-Schalter
MODEL:HGC MODEL:HGC303	Part No : R-95348-41-085
EN60947-5-1	
LJS-E7312	LIMIT SWITCH
	Range 0-10 KG/cm2 Max WP 35 kgf/cm2 Cal RNG 4mA-0-----

STG940-E1L-00000-W-E9	-20mA -10 kgf/cm Supply 11-42 VDC Design Pressure 0-8 kg/cm2 Working Temperature 175 °C
Y226	
FL2B-4J6	PROXIMITY SENSOR
HPJ-R22	
R4075341101	
R4075341041	
LDV-5402	
STEAM VALVE WITH POSITIONER	VALVE PROD. NO: R-08344-41-030 TAG NO: TCV9031 RANGE: 0,8-2,4 KGF/CM2 SUPPLY: 2,8 KGF/CM2 MODEL: AGVB SIZE: 2.1/2B POSITIONER MODEL: HEP 17-12BLRY3NNSD-A1-X INPUT: 4/20mA DC DATE: JUL 98 FLANGE PH2-VC8 2-1/2 10K-150 S
SL1.A	
SL1-E	
SL1-D	
APM-D3D1F	PROXIMITY SENSOR
SI1-D	LIMIT SWITCH
Ms052501y	
FI2s-4j6sd-Cn03	SENSOR Please look at the attachement
FI7m-3w6hwt-Cn03	
Vcx-7001	
En60947 - 5 - 1	
SI1-A	Limit Switch
Avp300-Fsd5b-1xxx-X	Smart Valve Positioner 300 Series Analog Signal(4 to 20mA.DC.) without travel transmission. FM Explosionproof and Flameproof Air piping connection : 1/4 NPT Electrical connection : 1/2 NPT Direct action Supply air : 450<Ps≤700kPa Scale unit : kgf/cm2 Model KZ03 Pressure Regulator with Filter
Hpj-T21	PHOTOELECTRIC SENSOR
072 4p SI I-M	Switch
FI7m 10j6w Cn03	
SI1-Dkl	
0736p Dc-12 5a-24v	SL1-HFXC2

Sta923-E1g-00000-7-E9	
Lds-5200k	
FI7m-7j6hw-Cn03	
Kk-0002-E-8000212	
FI7m-15y6w-910	
Fe7c-Twc6wr	
FI2r-4j6sd-L2	PROXIMITY SENSOR
Mtg18a-200pd2lseaaahx-Xx-K	
1ls1-Jgec	
Mgg18d-200p21ls5aaa-Xx-Y	FLOWTUBE METER 8IN 3000 PLUS
Mtg18a-100pd2csdaaahx-Xx-X	
FI7m-15w6w-Cn03b	
FI7m-2j6hd	
SI1-Akl	
Avp300-Fsd5b-1xxx-W	Smart Valve Positioner 300 Series Analog Signal(4 to 20mA.DC.) without travel transmission. FM Explosionproof and Flameproof Air piping connection : 1/4 NPT Electrical connection : 1/2 NPT Direct action Supply air : 450<Ps≤700kPa Scale unit : kgf/cm2 Model KZ03 Pressure Regulator with Filter Reversing Relay for double acting actuator
SI1-Hkl	
FI2-20b65	
FI7m-7j6hd-L5	
FI7m-1p5a6-Cn03 / Npn M8 Keine Näherungsschalter M12 Einsatzmaterial	
Avp200-Esd5b-15xx-Mu	Smart Valve Positioner 200 Series Analog Signal(4 to 20mA.DC.) without travel transmission TIIS Flameproof with cable gland Air piping connection : Rc1/4 Electrical connection : G1/2 Direct Action Supply air : 450<Ps≤700kPa Scale unit : kgf/cm2 Model KZ03 Pressure Regulator with Filter (Mounted on Positioner) cable length : 5m With terminal box for remote cable assembly (Standard) Stainless mounting kit of a positioner side and pressure regulator with filter
FI2-B-4j6-E	
FI7m-10k6we-910	
Fe8v-Ta6-903-Cn08	

Mgg18d-005p21ls5aaa-Xx-Y	ELECTRODE
Mgg14c-Cb4h-Xbxx-Yah	FLOW METER MAGNEW 3000 PLUS
Fe7c-Twc6we	
Fe8v-Ta6;	
Fl7m-10j6w-Cn03	
Fl7m-3j6hw-Cn03	
Sl1-Ek	LIMIT SWITCH