

Ytc

Garanti: 12 ay
Bu ürüne ait Türkiye içi
kapı teslim fiyat ve
teslim süresi içeren
teklifimizi almak için
info@yursat.com.tr e-
posta adresine
başvuru yapabilir ya
da ayrıntılı bilgi için
+90 224 240 03 04
numaralı
telefonumuzdan
bizlere ulaşabilirsiniz.
Ytc Markası, tedarik
süresi için lütfen
bizimle iletişime
geçiniz.

*Firmamız Ytc Türkiye
Distribütörü veya temsilcisi
değildir. Firmamız sipariş
durumunda, belirtilen
ürünlerde sadece Orjinal ve
yeni ürün teklifi sunmaktadır.
Bu sitede gösterilen Özel marka
adları ve ticari markalar ilgili
sahiplerinin mülkiyetindedir,
talep durumunda
kaldırılmaktadır.*



Ürün	Açıklama
YT-2500LSI2301S	Smart positioner YT-2500 Acting: Simple Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : 20...70 mm Air connection type : G1/4" Cable gland thread : G1/2" Communication: None Option: Feedback signal Temperature: -30 à 85°C Material : Aluminium Bracket included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
repair kit 310	
YT-310	Seri:31212729
YT-2500RSI5221S	Smart positioner YT-2500 Acting: Single Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : Namur Air connection type : NPT1/4" Cable gland thread : 1/2" NPT Communication: HART Option: Feedback signal Temperature: -30 à 85°C Material : Aluminium Bracket included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
	Electro-Pneumatic positioner YT-1000 Rotary Acting: Double Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : Diam 1 Connection type : PT1/4" Dome cover Option:

YT-1000RDN521S10	Without Température: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2.8 kg / 4.2 kg Dim : 27 x 20 x 20 cm
YT-1000RDN521S13	Electro-Pneumatic positioner YT-1000 Rotary Acting: Simple Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : 2 Connection type : PT1/4" Dome cover Option : Limit switch (Internal) Température: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 3.6 kg / 4.5 kg Dim : 30 x 20 x 30 cm
YT-1000RSN532S15	Electro-Pneumatic positioner YT-1000 Rotary Acting: Simple Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : None Connection type : NPT1/4" Dome cover Option : Feedback signal + Limit switch (Internal) Température: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 3.6 kg / 4.5 kg Dim : 30 x 20 x 30 cm
YT-310N1	Volume booster YT-310 N1 Connection : NPT 3/4" Pressure maxi : 10 B Pressure signal : 7 B maxi Température: -20 .. 70°C Material : Aluminium Net weight / Brut : 2.3 kg / 2.5 kg Dim : 18 x 14 x 14 cm Origine : South Korea Code HTS : 848110999
YT-1000RDN521S11	Electro-Pneumatic positioner YT-1000 Rotary Acting: Double Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : 2 Connection type : PT1/4" Dome cover Option : Feedback signal Température: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 3.6 kg / 4.5 kg Dim : 30 x 20 x 30 cm
YT-2501LSI2321S1	Smart positioner YT-2501 - Linear Acting: Single Input signal : 4-20 mA Ex-proof : ATEX -Ex ia IIC T5/T6 Gb Lever : 20 ~70 mm Air connection type : NPT1/4" Cable gland thread : ½" G Communication: HART Option: Feedback signal Feedback module : SPTM Température: -30 à 85°C Material : Aluminium No Included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
G1/4//YT-2500LSI2321S	
YT-2500LSI2321S	Smart positioner YT-2500 Acting: Single Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : 20...70 mm Air connection type : G 1/4" Cable gland thread : ½" G Communication: Hart Option: Feedback signal Température: - 30 à 85°C Material : Aluminium
YT-3303RSN1201S	Smart positioner YT-3300 Acting: Double Input signal : 4-20 mA Ex-proof : without Lever: M6 X 34 L Connection type : N1/4" Cable gland thread : ½" G Communication: HART Option: Without Température: -30 à 85°C Material : Aluminium Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
YT-3400RDC5103S	Smart positioner YT-3400 Acting: Double Input signal : 4 ~20 mA Ex-proof : Exd IIC T6 Lever : Namur Connection type : Rc 1/4" Cable gland thread : ½" Communication: without Option: Feedback signal & limit switch (Electronic version)

YT-2500RDI2121S	Température: -30 à 85°C Smart positioner YT-2500 Acting: Double Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : M6 X 63 L Connection type : Rc 1/4" Cable gland thread : ½" G Communication: Hart Option: Feedback signal Température: -30 à 85°C Material : Aluminium
Yt-400sn1	
Yt-205an110	
Yt-1000rdn521s10	
Yt-2500lsi1321s	
Yt-200an01	
Yt-310n1	
Yt-3300ldn4201s	
Yt-1000ldi111s0	
Yt-520s21	
Model: Yt-2500, Lsn2221 S	
Yt-200bn010	
Yt-200bn210	
Yt-320n1, Pro. Æ:12fa2, Max Air: 1mpa, Npt 1/2	
Yt-300 Not Complete	
Yt-520d22	
Yt-320n1	
Yt-1000rdm522s10	
Yt-1000ldm231s0	
E / P Switch Positioner For Model : Yt 1000 Rdn 52110	
Yt-1000 Ldm231so S/N:K0513997	
Repair Kit For Yt-310	
Yt-1000rdn521s13	
Yt-300p1	
Yt-300 Volume-Enhancing, Repair And Maintenance Kit	
Yt-200	

Yt-2500Isi1322s	
E / P Positioner For Model : Yt 1000 Rdn 52110	
Yt-850m411	
Yt-300n1	
Yt-1000 Rdn13114 Ra - , By Yt-1000 Rdn131s14	
Yt-1000lsm111s3	
Yt-200 Repair Kit For Air Filter Regulator	
Yt-310n	
Yt-320-N2	
Yt-2500Isn120 4s	
Yt-1000rdn531s13	
Electro Pneumatik Rotary Positioner Yt-1000 Rdm	S/N 12051781 1 set will be use with 4 " butterfly valve and 1 set will be use with 3" Butterfly valve Please see attached Photo
Yt-3450	