



Cla-Val

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Cla-Val Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Cla-Val Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
2050b-4kg1	CV050100A11506-1 Fire pressure relief valve Angle pattern DN150 (6") / ANSI 150 RF UI listed FM approved 213 kg 83x83x90
*Cv050100a11507-Sws/B	Fire pressure relief valve CLA-VAL 2050B-4KG1/SWS(angle) DTBTB , DN150 / ANSI 300RF Epoxy RAL 3000 (red) CRL : 7,0-21,0 bar [10,0bar] UL approved
SOL090-005/UL	Pressure reducing control CLA-VAL CRD/KX1 Rp 3/8" PN25 2,1 - 11,6 bar (5,0bar) For use on UL listed valves 90-21class ANSI300
22217-18G	Repair Kit for main valve CLA-VAL Model 100G Size DN 200 (8") NBR diaphragm NBR disc NBR O-ring Fiber Space Washer
SOL090-005/UL	Pressure reducing control CLA-VAL CRD/KX1 Rp 3/8" PN25 2,1 - 11,6 bar(4,8bar) For use on UL listed valves 90-21 class ANSI300
50B-4KG1X Fire Protection Pressure Relief Valve	Size matters: Size: inlet(in) \ outlet(in) 1.1/2"
300347-V13-BS-D-10	Pressure holding control valve CLA-VAL 55L-60 3/4 "NPT / PN25 7.0 -21.0 bar (7.0 bar)
1" (3410AR-116.3)	
3/4" UL/FM	
6" 300PSİ UL/FM	
55L-60 3/4"NPT / PN 16	300347-V13-BS-C-10 Pressure relief control CLA-VAL 1,4-14,0bar [5,0bar] UL / FM approved
CLA-VAL 55L-60	Pressure releif valve 1/2" NPTF / PN16 UL listed FM approved Bronze / BUNA Pressure range 1.4 - 14.0 bar (factory preset 5.0bar)
NG1E-124-01 / KCHOS , DN 100/PN 10-	*CV124001N11002-KCHOS ON - OFF float control valve with float installed on valve CLA-VAL CF1-C1 + 1 x valve position

16	indicator + x gauge cock upstream CSA-12 , Rp1/21 and manometer Rp 1/2" (0-16bar)
CV090021G12007	Pressure reducing valve CLA-VAL 90G-21(globe) , DN200 / ANSI 300RF CRD : 30-165 PSI (2.1 - 11.6 bar) preset at 70 Psi. Epoxy coated RED RAL 3000 UL approved
DN200 MONITORING SWITCH BUTTERFLY VALVE	
V-5544B	EPDM Diaphragm GE 300 / PN 10-16
300889-150	EPDM Diaphragm GE 150 / NGE 200 PN 10-16
PRV-1A 6 PRESS REG FxF PN	
PRV-1A 8 PRESS REG FxF PN	
2991201B	
2991801J	
01240B	
6799317A	
2993501C	
01243F	
00529J	
21223101J	
6774604A	
6818505H	
601217	Repair Gasket Kit 341GF 202139-01F 2991201B NOSE SEAL ASSY 2991801J BUMPERS 01240B O RING 6799317A PIN, COTTER 2993501C GUARD 01243F O RING 00529J O RING 21223401JPIN 6774604A WSHR 6818505H RING 00590A O RING 01242H O RING 1 of each included
212234-01J	Link Pin for C-Clip
6774604A	Washer
352GF	
DN150	
58845-51-NM	Air Release & Vacuum Breaker Valve Model 33A Screwed 2" NPT ASTM B148 NiA1Bz and cover Monel float & trim NBR rubber parts
20035609H 100-300	
20035609H	BS/BUNA pressure relief valve CLA-VAL 55-L, NPT 3/4" - PN 25 100-300PSI(7,0-21,0 BAR) FM Approved

02-10 Inpsection Certificate300347-V13-BS-D-10

Pressure Relief Valve Model 55L-60 3/4" NPTF -PN25 UL Listed FM approved Body&Cover: Bronze Trim: Stainless Steel Rubber: NBR Pressure Range: 7.0 - 21.0 bar [factory preset 7.0 bar] Pressure Range: 100-300 psi [factory preset 100psi]

CV090021G10656

Pressure Reducing Valve 90G-21 Globe Dn65 (2 1/2") ANSI 150RF UL listed Ductile iron ASTM A536 main valve Fusion bounded epoxy coated RAL 3000(red) CRD: 30-165psi (2.1-11.6 bar) factory pressure preset 70psi (4.8bar)

CV090021G11006

Pressure Reducing Valve 90G-21 Globe DN100 (4") ANSI 150RF UL listed Ductile iron ASTM A536 main valve Fusion bounded epoxy coated RAL 3000(red) CRD: 30-165psi (2.1-11.6 bar) factory pressure preset 70psi (4.8bar)

*CV050100A12007/B

Model 2050B-4KG1(angle) Pressure Relief Valve DN200 (8") ANSI 300RF UIL listed FM approved

21005206G

Pressure relief Valve Model 55L-60 1" NPTF-PN25

Pressure Relief Valve Model 55L-60

3/4" NPTF -PN25 300347-V13-BS-D-10

204890-01A

Crank Shaft

29904-01J

Crank Shaft Bushing

Cap Cla-Val ISO45 PUR with fastening rope

603122

C-34222700203K

3410AR116.3 1"NPT Outlet 1/2" NPT 300psi

SOL090-005/UL

CRD/KX1 Rp 3/8" /PN25 2,1-11,6bar [5,0 bar] For use on UL listed valves 90-21 class ANSI 300

CV050100G12006

Model 50B-4KG1 DN200(8")/ ANSI 150RF UL listed FM approved Main valve ductile iron ASTM A536 fusion bounded epoxy coated (internal/external) red RAL3000 CRL-60: 1,4-14,0 bar

DN80 PN16 DELUGE VALVEDN100 PN16 DELUGE VALVEDN150 PN16 DELUGE VALVE21056731D

Air Release Valve - Simple Lever Type CLA-VAL Model 3410AR-116.3 Inlet size: 1" NPTF Outlet size: 1/2" NPTF (1" Size Supplies Std. with 1/2" & 3/4" Bushing Included) Orifice size: 1/16" Pressure rating: 300 psi Ductile Iron ASTM A536 body fusion bounded epoxy coated red RAL 3000 (ext) Stainless steel trim & float FM approved UL listed

SOLO90-005/UL - CRD3/8 KX121-11.6 BAR-PRESET

(4,8) BAR - CRD 3/8)

21056731D	Air Release Valve - Simple Lever Type CLA-VAL Model 3410AR-116.3 Inlet size: 1" NPTF Outlet size: 1/2" NPTF (1" Size Supplies Std. with 1/2" & 3/4" Bushing Included) Orifice size: 1/16" Pressure rating: 300 psi Ductile Iron ASTM A536 body fusion bounded epoxy coated red RAL 3000 (ext) Stainless steel trim & float FM approved UL listed
SOL090-005/UL	Pressure reducing control CRD/KX1 Rp 3/8" PN25 2,1 - 11,6 bar (5,0bar) For use on UL listed valves 90-21class ANSI300
3410AR-116.3	AIR RELIEF VALVE-FM
CL469DJL-Anti Water Hammer Valve	DN100 PN16
(3/4")	diaphragm gasket
IALIFT34-200-01	Analogical lift sensor e-Lift-34 GE200/NGE 250, 12-24 V/DC IP68 Junction box Z101/SS +2x option for X105 Sensor 10m on e-Lift 34
IALIFT34-100-01	Analogical lift sensor e-Lift-34 GE100/NGE 125-150, 12-24 V/DC IP68 Junction box Z101/SS +2x option for X105 Sensor 10m on e-Lift 34
90A/G-21	CV090021G11009/ DN100 /ANSI 300 psi DN100/ 4"
90A/G-21 ANSI 300 psi/	DN150
6quot;Druckreduzierventil	
2991201b	
3450-Ar116	
134/05 2??	
35-Ww 2	
55f 3/4?	
100gs	
20071003e Str Assy 344gf100m 300	
2100 G	
Set Of Inspection Certificate En 10204-3.1	- material certificate for valve body and cover - pressure test certificate - conformity certificate
50a-20	
300041-Wm-L10-N200-Dpc-R-T02	
55L-60 3/4"npt / Pn 25	Pressure relief valve CLA-VAL 55L-60 3/4"NPT / PN 25 7,0 - 21,0 bar [7,0 bar] UL / FM approved Part number: 300347-V13-BS-D-10 Country of origin: Switzerland Custom tariff no : 8481.8090
2quot; Druckreduzierventil	

55f 3/4?- Ss316- H185- Set Pressure 1,4 - 14 Bar- Pn 25	
4quot; Druckreduzierventil	
Cla-Val 340af	Pressure Fuel Servicing Adapter
Ã39;6 Quot;- Differenzdruck Einstellbereich 3-10 Bar	
380-Dn 25	
29028054	
22422a	
Ã39;3 Quot;- Differenzdruck Einstellbereich 3-10 Bar	
790-01	
90g-21 (Globe) 1 ½" Scewed	Pressure reducing valve CLA-VAL ANSI 150RF CRD: 30 - 165 PSI (2.1 - 11.6 bar) preset at 70 PSI Epoxy coated RED RAL 3000 UL approved Unit net weight : estimated 11.0 Kg
50b-4kg1	
50-G1e-48cgs Dn 50 / Ansi 150rf	
730-01	
300347-V13-Bs-C-10	Pressure relief control CLA-VAL 55L-60 3/4"NPT / PN 16 1,4 - 14,0 bar [5,0 bar] UL / FM approved Net weight per piece : 2 kg/pce Country of origin: Switzerland Custom tariff no : 8481.8090
134/83 3??	
134-G1e-05msy	"ON - OFF" solenoid DELUGE control valve CLA-VAL Model 134-G1E-05MSY DN 250 / Class ANSI 150RF
1quot; Series 33a	
341gf-Vd3ssbvm100g30	
58754-32	
8quot; Circulation Relief Valves	
8quot; Main Relief Valves	
8quot; Druckreduzierventil	
58754-23	
3quot; Druckreduzierer	
2050b 4kg 4?	
40-28ags W/Rofc Al/Ss/Ss 6	

690-01	
3m Ir 1100	
20213901f Kit, Rppt 341gf 2ha	
6 "pressure Reducer Valve, Locked, 300 Psi	
698-06	
100af	
90g-21 (Globe) Dn 100	Pressure reducing valve ANSI 150RF CRD: 30 - 165 PSI (2.1 - 11.6 bar) preset at 70 PSI Epoxy coated RED RAL 3000 UL approved Unit net weight : estimated 56.0 Kg
20389702e Kit, Rppt D-3 2has	
2" Hava Tahliye Vanasi, 500psi, Ductil Döküm.Model 33a,	